

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



B10

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> :  
E05B 65/19, E05F 1/08

A1

(11) International Publication Number: WO 97/01010

(43) International Publication Date: 9 January 1997 (09.01.97)

(21) International Application Number: PCT/GB96/01453

(22) International Filing Date: 18 June 1996 (18.06.96)

(30) Priority Data:  
9512816.1 23 June 1995 (23.06.95) GB

(71) Applicant (for all designated States except US): DRAFTEX INDUSTRIES LIMITED [GB/GB]; 11 Glenfinlas Street, Edinburgh EH3 6YY (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): GALLAS, Gérard [FR/FR]; 46, boulevard des Poilus, F-44300 Nantes (FR).


(74) Agent: MATHISEN MACARA & CO.; The Coach House, 6-8 Swakeleys Road, Ickenham, Uxbridge, Middlesex UB10 8BZ (GB).

(81) Designated States: US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: OPENING ARRANGEMENTS AND METHODS FOR CLOSURE MEMBERS



(57) Abstract

An arrangement and method for remotely unlocking and raising the hatchback (12) of a motor vehicle (10) is described. Firstly, a signal (24) is sent to unlock and unlatch the vehicle hatchback (12). The unlatched hatchback (12) is automatically raised by an amount sufficient to allow gas springs (18) to complete the raising operation. The gas springs (18) may incorporate a device to prevent the hatchback being fully raised.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

OPENING ARRANGEMENTS AND METHODS FOR CLOSURE MEMBERS

The invention relates to a closure opening method, comprising the steps of emitting a signal from a remote location; detecting the signal; and causing an unlatching mechanism to be operated.

The invention further relates to a remotely operable closure opening arrangement, comprising a releasable latching mechanism for latching the closure in the closed position, signal emitting means for emitting an opening signal from a remote location, and detecting means for detecting the signal and releasing the latching mechanism.

Such arrangements and methods are shown in US 4,796,932. In this system, for remotely releasing a motor vehicle compartment panel, a remote release and pull down unit is provided which allows the panel to be unlatched and pulled down enabling the user to unlatch and latch the panel remotely. However, it is desirable to produce a closure opening arrangement in which the panel is opened by a predetermined amount in a controlled fashion.

Accordingly, the known method is characterised by the steps of opening the closure to an initial extent sufficient for a controlled opening mechanism to become operative and causing the closure to be opened by the controlled opening mechanism to a predetermined greater extent.

Furthermore, the known arrangement is characterised by initial opening means responsive to release of the latching mechanism to open the closure to an initial position, and a controlled opening

mechanism operative to open the closure from the initial partially open position to a predetermined greater extent.

Hatchback and luggage compartment opening arrangements, embodying the invention, for use in motor vehicles will now be described, by way of example only, with reference to the accompanying diagrammatic drawings in which:

Figure 1 is a side view of the rear of a motor vehicle showing the hatchback in a closed position;

Figure 2 is a side view of the rear of a motor vehicle showing the hatchback in a fully raised position; and

Figure 3 is a schematic block diagram of the controls of an embodiment of the invention.

The motor vehicle 10 has a hatchback 12 pivotally attached to the body of the vehicle 14 by hinges 16. The hatchback 12 is retained in the closed position by means of a latch and a locking mechanism 20. The latch and locking mechanism 20 can be operated remotely by a portable key device 22 (see Figure 3).

Gas springs 18 (Figure 2, which shows only one of the gas springs) are provided for lifting the hatchback 12 and retaining it in the open position.

To open the hatchback, in accordance with the invention, the operator presses the appropriate button on the separate key device. A suitable signal (such as an infra-red or radio signal) is accordingly emitted by the key device 22 which in turn is

detected by a detector 26. The detector 26 emits a signal on a line 30 that activates a component 32 to unlock the latch mechanism 20.

A spring 34 or any other suitable means then raises the unlatched hatchback 12 slightly and to a level where the gas springs 18 can become operative and raise the hatchback.

The control unit 32 can be part of the central door locking system. However, preferably it can cause the hatchback to open independently of the other vehicle doors.

Additionally, the key device 22 may have other functions such as unlocking the central door locking or arming the vehicle alarm and need not be solely for raising the hatchback.

Furthermore, it will be appreciated that the vehicle need not be a hatchback motor vehicle, and the vehicle part to be opened need not be the hatchback, but could for example be another closure member which is opened by a gas spring or similar means when unlatched, such as the lid of a luggage compartment.

In a modified embodiment of the invention, the gas springs 18 allow the hatchback 12 to be raised only to a certain predetermined intermediate level less than the fully open position. This reduces the risk that the hatchback 12 will be damaged by contacting a low roof or other obstruction. The hatchback can thereafter be caused to rise to the fully open position if desired, by manual force or by further unlatching action.

CLAIMS

1. A closure opening method, comprising the steps of emitting a signal (24) from a remote location; detecting the signal (24); and causing an unlatching mechanism (20) to be operated; characterised by the steps of opening the closure (12) to an initial extent sufficient for a controlled opening mechanism (18) to become operative; and causing the closure (12) to be opened by the controlled opening mechanism (18) to a predetermined greater extent.
2. A method according to claim 1, characterised in that the predetermined extent to which the closure (12) is opened by the controlled opening mechanism (18) is less than the fullest extent of opening.
3. A method according to claim 2, characterised in that the closure (12) can be opened to the fullest extent from the predetermined extent.
4. A remotely operable closure opening arrangement, comprising a releasable latching mechanism (20) for latching the closure in the closed position, signal emitting means (22) for emitting an opening signal (24) from a remote location, and detecting means (26) for detecting the signal (24) and releasing the latching mechanism (20), characterised by initial opening means (34) responsive to release of the latching mechanism (20) to open the closure (12) to an initial position, and a controlled opening mechanism (18) operative to open the closure from the initial partially open position to a predetermined greater extent.

5. An arrangement according to claim 4, characterised in that the predetermined greater extent to which the closure (12) is opened by the controlled opening mechanism (18) is less than the fullest extent of opening.
6. An arrangement according to claim 5, characterised in that the closure (12) can be opened to the fullest extent from the predetermined extent.
7. An arrangement or method according to any preceding claim characterised in that the signal (24) is an infra-red signal.
8. An arrangement or method according to any preceding claim characterised in that the signal (24) is a radio signal.
9. An arrangement or method according to any preceding claim, characterised in that the unlatching mechanism (20) is part of a central door locking system in a motor vehicle (14).
10. An arrangement or method according to any preceding claim, characterised in that the closure (12) is opened to the initial extent by a spring mechanism (34).
11. An arrangement or method according to any preceding claim, characterised in that the initial opening means (34) is an electric actuator.
12. An arrangement or method according to any preceding claim, characterised in that the controlled opening mechanism (18) is a gas spring.

13. An arrangement or method according to any preceding claim, characterised in that the closure (12) is an openable motor vehicle door or lid.

14. An arrangement according to claim 13, characterised in that the door is a hatchback (12).



1/2




Fig. 1





Fig. 2

2/2

*Fig. 3*

# INTERNATIONAL SEARCH REPORT

Inventor's Application No  
PCT/GB 96/01453

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 E05B65/19 E05F1/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 E05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US,A,4 739 585 (PICKLES) 26 April 1988	1,4,10,
Y	see the whole document	11
		2,3,5-9,
		12
Y	--- WO,A,92 14018 (AUDI AG) 20 August 1992	2,3,5,6,
	see the whole document	12
Y	--- DE,A,42 18 798 (MERCEDES BENZ AG) 9 December 1993	7-9
	see the whole document	
X	--- US,A,4 746 153 (COMPEU ET AL.) 24 May 1988	1,4,11
	see the whole document	
	---	
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*&\* document member of the same patent family

Date of the actual completion of the international search

6 September 1996

Date of mailing of the international search report

19.09.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Westin, K

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 96/01453

## C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US,A,3 835 678 (MEYER ET AL.) 17 September 1974 see the whole document	1,4,11
X	US,A,3 081 078 (LOHR) 12 March 1963 see the whole document	1,4,11
A	DE,A,43 21 586 (OHI SEISAHUSHO CO., LTD.) 5 January 1994 see the whole document	1,4,12

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 96/01453

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4739585	26-04-88	DE-A- 3815065	23-11-89
		JP-A- 63197785	16-08-88
-----	-----	-----	-----
WO-A-9214018	20-08-92	DE-A- 4103521	13-08-92
-----	-----	-----	-----
DE-A-4218798	09-12-93	NONE	
-----	-----	-----	-----
US-A-4746153	24-05-88	CA-A- 1304591	07-07-92
		DE-A- 3817597	08-12-88
		GB-A,B 2204913	23-11-88
		JP-A- 63312484	20-12-88
		US-E- RE33758	03-12-91
-----	-----	-----	-----
US-A-3835678	17-09-74	CA-A- 1002996	04-01-77
-----	-----	-----	-----
US-A-3081078	12-03-63	NONE	
-----	-----	-----	-----
DE-A-4321586	05-01-94	US-A- 5411302	02-05-95
-----	-----	-----	-----

**This Page Blank (uspto)**